

MHI
Copy 3

FM 2-6

WAR DEPARTMENT FIELD MANUAL

REGRADED UNCLASSIFIED BY
AUTHORITY OF DOD DIR. 5200.1 R
BY RAHRS ON 8-11-2003

CREW DRILL LIGHT ARMORED CAR

M8

**MHC
COPY** /

~~This is a~~ reprint for stock only and
will not be issued to individuals
possessing the original publication.

DISSEMINATION OF RESTRICTED MATTER.—No
person is entitled solely by virtue of his grade or position to
knowledge or possession of classified matter. Such matter
is entrusted only to those individuals whose official duties
require such knowledge or possession. (See also AR 380-5.)

WAR DEPARTMENT • DECEMBER 1943

CREW DRILL LIGHT ARMORED CAR M8



WAR DEPARTMENT • DECEMBER 1943

RESTRICTED DISSEMINATION OF RESTRICTED MATTER.—No person is entitled solely by virtue of his grade or position to knowledge or possession of classified matter. Such matter is entrusted only to those individuals whose official duties require such knowledge or possession. (See also AR 380-5.)

WAR DEPARTMENT,
WASHINGTON 25, D. C., 30 December 1943.

FM 2-6, Cavalry Field Manual, Crew Drill, Light Armored Car M8, is published for the information and guidance of all concerned.

[A. G. 300.7 (16 Nov 1943).]

BY ORDER OF THE SECRETARY OF WAR:

G. C. MARSHALL,
Chief of Staff,

OFFICIAL:

J. A. ULIO,
Major General,
The Adjutant General.

DISTRIBUTION:

D 2, 7, 17 (5); Bn and H 2, 18 (5); IC 2, 18 (20).
(For explanation of symbols see FM 21-6.)



TABLE OF CONTENTS

	Paragraphs	Page
SECTION I. General.....	1-2	1
II. Crew composition and formations.....	3-4	2
III. Crew control.....	5-6	3
IV. Crew drill.....	7-11	7
V. Signals	12	9
VI. Dismounted action.....	13-14	9
VII. Inspections	15	10
VIII. Service of 37-mm gun.....	16-22	10
IX. Mounted action.....	23-27	13
X. Special situations.....	28-29	14
XI. Destruction of equipment.....	30-33	15
APPENDIX.....		17

CREW DRILL, LIGHT ARMORED CAR M8

SECTION I

GENERAL

■ 1. **PURPOSE AND SCOPE.**—*a.* This manual is designed for the use of the platoon leader and car commander in training members of the crew of the light armored car M8. (See fig. 1.) It is to be used as a guide to achieve orderly, disciplined, and efficient execution of mounted and dismounted action, and precision, accuracy, and speed in the service of the vehicular weapons.

b. Reference is made to other War Department publications where appropriate. A complete list is contained in FM 21-6.

■ 2. **TRAINING PRINCIPLE.**—Training in crew drill will stress the importance of the prompt execution of correct movements at all times. Strict adherence to standardized procedures during the training period will insure the smooth functioning of the crew as a team in critical combat situations.




FIGURE 1.—Light armored car M8.

SECTION II

CREW COMPOSITION AND FORMATIONS

■ 3. COMPOSITION.—The crew of the light armored car M8 consists of four members, a car commander, a radio operator and assistant driver (hereafter referred to as radio operator), a driver, and a radio operator and gunner (hereafter referred to as gunner). The car commander may be an officer or a noncommissioned officer.

■ 4. FORMATIONS.—*a. Dismounted posts.*—The crew forms in one rank. (See fig. 2.) The car commander takes his post three paces in front of the right front wheel, facing to the front. The radio operator, driver, and gunner, in that order, take posts on the left of the car commander at close interval (4 inches).




FIGURE 2.—Dismounted posts.




FIGURE 3.—Method of mounting.

b. Mounted posts.—The crew forms mounted as follows (see fig. 4):

- (1) *Car commander.*—On the right side of the turret, standing on the floor, or sitting or standing on the turret seat.
- (2) *Radio operator.*—In the assistant driver's seat.
- (3) *Driver.*—In the driver's seat.
- (4) *Gunner.*—On the left side of the turret, standing on the floor, or sitting or standing on the turret seat.

SECTION III

CREW CONTROL

■ 5. OPERATION OF INTERPHONE.—*a.* The interphone is used whenever the car is operated. After mounting, headsets and

microphones are put on and tested according to the procedure outlined in paragraph 1 of the appendix.

b. In connecting the break-away plug, each crew member inserts the plug of the short cord extending from his headset, into the break-away plug of the extension cord of his interphone control box. The throat microphone is adjusted so that the microphone buttons fit firmly on the front part of the operator's neck, and is connected to the break-away plug on the extension cord. During the procedure of checking interphone, each crew member adjusts the volume control on his interphone control box to the desired level. Care must be taken that the microphone switch does not remain in a locked position.

c. It is the duty of each man invariably to check his personal interphone equipment upon mounting. He ascertains that it is properly maintained and reports malfunctions to the car commander.

d. Definite commands and terminology are set forth in paragraph 6. These terms, and such others as are standardized by individual units, are used in order to insure speed and accuracy in the transmission of orders. General conversation on the interphone causes misunderstanding and disorder and is detrimental to discipline.

■ 6. INTERPHONE LANGUAGE.—a. *Terms.*

Car commander-----	LIEUTENANT or SERGEANT
Radio operator-----	RAD
Driver-----	DRIVER
Gunner-----	GUNNER
Any unarmored car---	CAR
Armored car-----	ARMORED CAR
Any unarmored truck--	TRUCK
Any antitank gun-----	ANTITANK
Infantry-----	DOUGHS
Machine gun-----	MACHINE GUN
Airplane-----	PLANE
Tank-----	TANK
Mines-----	MINES
Ditch-----	DITCH




FIGURE 4.—Crew at MOUNTED POSTS.

b. Commands for movement of car (see also FM 2-5).

To move forward-----	DRIVER MOVE OUT
To halt-----	DRIVER STOP
To reverse-----	DRIVER REVERSE
To decrease speed-----	DRIVER SLOW DOWN
To turn right 90°-----	DRIVER CLOCK 3, STEADY ON
To turn left 60°-----	DRIVER CLOCK 10, STEADY ON
To turn right (left) 180°-----	DRIVER, CLOCK 6 RIGHT (LEFT), STEADY ON
To have driver move toward a terrain feature or reference point, the car being headed in proper direction-----	DRIVER MARCH ON WHITE HOUSE (HILL, DEAD TREE, ETC.)
To follow in column--	DRIVER FOLLOW THAT CAR (DRIVER FOLLOW CAR NO. --)
To follow on road or trail-----	DRIVER RIGHT ON ROAD (DRIVER RIGHT ON TRAIL)
To start engine-----	DRIVER CRANK UP
To stop engine-----	DRIVER CUT ENGINE
To proceed in a spe- cific gear-----	DRIVER THIRD GEAR (FIRST GEAR) (FOURTH GEAR)
To proceed at same speed-----	DRIVER STEADY

c. Commands for control of turret.

To traverse turret----- GUNNER TRAVERSE LEFT
(RIGHT) (REAR)

To stop turret trav-
erse----- GUNNER STEADY, ON

d. Fire orders.—See FM 23-50 and 23-81.

SECTION IV

CREW DRILL

■ 7. To FORM CREW.—*a. Crew being dismounted.*—At the command DISMOUNTED POSTS, FALL IN, crew takes dismounted posts (see par. 4a and fig. 2). In falling in, crew members dress automatically on the car commander at close interval and then come to attention without command.

b. Crew being at dismounted posts.—At the command FALL OUT, the crew breaks ranks. Members habitually fall out to the right of the car.

c. Crew being at dismounted posts.—At the command CALL OFF, the members of the crew call off in turn as follows:

- (1) Car commander----- SERGEANT (or LIEUTENANT).
- (2) Radio operator----- RAD.
- (3) Driver----- DRIVER.
- (4) Gunner----- GUNNER.

d. Crew being at dismounted posts.—To change designations and duties, the command is: FALL OUT SERGEANT (RAD) (GUNNER).

- (1) At the command—

(a) The man designated to fall out moves by the rear to the left flank position and becomes gunner.

(b) The crew members on the left of the vacated post move smartly to the right one position and prepare to call off their new designations.

(c) The crew member occupying the car commander's post starts calling off as soon the the crew is re-formed in line.

(2) The movement may be executed by ordering any member of the crew except the gunner to fall out.

(3) The movement should be executed with snap and precision at double time.

■ 8. To MOUNT CREW.—*a.* The crew, being at dismounted posts or dismounted, is mounted at the command or signal MOUNT. At the command or signal, crew members mount as prescribed in paragraph 1 of the appendix. (See also figs. 3 and 4.) During early stages of training, mounting should be done “by the numbers.”

b. Crew drill is conducted habitually with the gun cover of the 37-mm gun and the coaxial machine gun removed. Both hatch top covers will clear the guns if the turret traverse is set between 0 and 1 Left. The exact turret setting for each vehicle should be determined by the gunner and the traverse habitually placed on that setting before the gunner dismounts from the vehicle. Under special circumstances, when it is desired to leave the muzzle cover on during crew drill, the 37-mm gun is carried in a position between 0 and 1 Right to enable the driver's hatch top cover to clear.

■ 9. To CLOSE HATCHES.—At the command CLOSE HATCHES, the crew proceeds as outlined in paragraph 2 of the appendix.

■ 10. To OPEN HATCHES.—At the command OPEN HATCHES, the crew proceeds as outlined in paragraph 3 of the appendix.

■ 11. To DISMOUNT CREW.—*a.* The crew, being at mounted posts with hatch front covers open, is dismounted without vehicular weapons at the command or signal DISMOUNT. The crew proceeds as outlined in paragraph 4 of the appendix.

NOTE.—If the gun cover is left on the guns, it will be necessary for the gunner to move the turret sufficiently to the left to enable radio operator to open his hatch top cover after the driver has opened his. (See par. 8b.)

b. When the radio is to be used, the radio operator or the gunner remains in the car. The command for this is: EXCEPT RAD (GUNNER) DISMOUNT.

c. The crew habitually dismounts wearing helmets and carrying individual weapons.

SECTION V

SIGNALS

■ 12. VISUAL SIGNALS.—*a. Flag signals.*—(1) Each armored car normally carries three solid color flags, red, green, and orange.

(2) Flags are displayed vertically through the turret and may be moved to attract attention, or held stationary.

(3) The meanings of the signals are as follows:

Red—Enemy in sight.

Green—All clear, ready, or understood.

Orange—Out of action or disregard my actions.

Green and orange—Assemble, or close.

Red and green—Disperse.

Red, green, and orange—Gas.

(4) Additional signals may be improvised.

(5) The commands conveyed by the flag signals are executed as soon as they are understood.

(6) All subordinates are required to repeat flag signals as soon as they are understood.

b. Other visual signals.—Arm-and-hand, light, fire control, driver's, and pyrotechnic signals are discussed in detail in FM 2-7 (when published).

SECTION VI

DISMOUNTED ACTION

■ 13. TO FIGHT ON FOOT.—At the command or signal FIGHT ON FOOT, the crew proceeds as outlined in paragraph 5 of the appendix.

■ 14. TO REMOUNT.—*a.* At the car commander's signal OUT OF ACTION, the machine gun is taken out of action as prescribed in FM 23-45. If the driver has moved the vehicle to cover, the car commander signals BRING UP THE VEHICLE. The crew is mounted as prescribed in paragraph 8.

b. After mounting, the crew replaces the weapons and ammunition which were removed for dismounted action.

SECTION VII

INSPECTIONS

■ 15. GENERAL.—*a.* To insure mechanical efficiency it is necessary that the armored car systematically receive preventive maintenance and inspections at regular intervals. The car commander is responsible for seeing that all inspections are made. He aids in making inspections and receives the reports from the various crew members relative to their individual inspections. He indicates in his report anything requiring the services of maintenance personnel. In supervising first echelon maintenance he uses his discretion in delegating responsibility to other crew members.

b. The Driver's Report must be prepared carefully and thoroughly. Any irregularity previously reported which is not repaired before the car is used again is reentered on subsequent reports until such time as it has been corrected.

c. For crew duties in performing inspection and maintenance before operation, inspection during operation, inspection at the halt, and inspection after operation, see paragraphs 6 to 9, inclusive, of the appendix.

SECTION VIII

SERVICE OF 37-MM GUN

■ 16. GENERAL.—The gun crew of the 37-mm antitank gun consists of the gunner who aims and fires the piece, and the car commander who controls and adjusts fire and also acts as assistant gunner and loader. See paragraphs 10 to 14, inclusive, of the appendix for duties of crew in serving the turret guns. (See fig. 5.)

■ 17. LOADING.—The car commander grasps the cartridge at the base with his left hand, turns the projectile to the front, swings his arm toward the breech, and inserts the round in the opening. After the nose of the projectile enters the chamber, he propels the round forward by a quick push with his thumb and fingers on the base of the round, and moves the arm upward to clear the closing breechblock. (See fig. 6. Note position of fingers.) He then touches the leg of

except in combat. The breech is left open and the gunner takes post to receive the round as it is pushed out of the chamber. The car commander, using the rammer staff, rams the round out. The round should be shoved out of the gun with a steady pressure. If this does not suffice, the rammer may be tapped gently with a light block of wood. If the round cannot be removed by this procedure, experienced ordnance personnel should be called.

■ **21. MALFUNCTIONS.**—A malfunction of the gun or the ammunition causes a temporary cessation of fire. Most malfunctions can be prevented by proper care and cleaning of gun and ammunition. Immediate action is the procedure followed in order to correct the malfunction promptly. The causes of and immediate action for the various malfunctions of the 37-mm gun M6 are set forth in FM 23-81.

■ **22. CARE AND CLEANING.**—The vital importance of proper care and maintenance of vehicular weapons must be stressed throughout crew training. See FM 23-81 and FM 23-50.

SECTION IX

MOUNTED ACTION

■ **23. TO LOAD WEAPONS.**—Normally, the 37-mm gun is left unloaded, with breechblock closed, until the actual fire order is given. The car commander then loads the gun. The machine gun is kept half loaded during the approach march, when action is not imminent, and in bivouac. It is kept fully loaded at all times when there is any likelihood of the appearance of enemy targets.

■ **24. DUTIES IN FIRING.**—*a.* The car being prepared for action and the weapons loaded, at the command FIRE each crew member executes such of the duties enumerated in paragraph 11 of the appendix as will insure the continued firing of weapons and operation of the car.

b. Driver.—(1) *When car is moving.*—(a) The driver continues to drive in the direction indicated by the car commander. He operates the car at a constant speed, avoiding acceleration and deceleration as much as possible. He does

not deviate from the designated course except to avoid large obstacles or to change course as directed by the car commander. When the car is about to pass over rough ground or make a necessary change of course, the driver warns the gunner by calling "Rough" or "Changing course." Even though the car is slightly off the most advantageous course at the moment, the driver does not make any correction since even a small change in direction will upset the gunner's tracking.

(b) If the car commander does not order a gear ratio, the driver selects a gear ratio which will permit maintenance of the ordered constant speed consistent with the variations of the particular terrain. If the car commander announces the gear, the driver drives at the ordered speed or at a selected speed consistent with the terrain.

(2) *When car is not moving.*—(a) The driver keeps the vehicle in readiness to move promptly on order of the car commander.

(b) He observes the sector assigned by the car commander and reports targets to the car commander.

■ 25. **TO SUSPEND FIRING.**—At the command or signal **SUSPEND FIRING**, firing is stopped as prescribed in paragraph 12 of the appendix.

■ 26. **TO CEASE FIRING.**—At the command **CEASE FIRING**, the crew proceeds as outlined in paragraph 13 of the appendix.

■ 27. **TO SECURE EQUIPMENT.**—At the command **SECURE EQUIPMENT**, the crew proceeds as outlined in paragraph 14 of the appendix.

SECTION X

SPECIAL SITUATIONS

■ 28. **ACTION IN CASE OF FIRE.**—The first crew member to discover a fire gives the alarm, announcing the location of the fire; example, **ENGINE FIRE (HULL FIRE)**. Crew members proceed as follows: The driver takes the hand fire extinguisher and directs it on the fire. Other members of the crew will assist in combating the fire until further progress seems impossible. They dismount only on order of the car com-

mander. When time permits, the crew, in abandoning the vehicle, removes the 37-mm gun sight, the machine gun(s), carbines, grenades, and as much ammunition as possible.

■ 29. TO ABANDON VEHICLE.—At the command ABANDON VEHICLE, crew members follow procedure prescribed in paragraph 5 of the appendix, to fight on foot, except that all available caliber .30 machine-gun ammunition and hand grenades are removed from the car, if the situation permits, as a reserve supply for the crew. If practicable, wounded personnel are removed.

SECTION XI

DESTRUCTION OF EQUIPMENT

■ 30. GENERAL.—*a.* Situations may arise when matériel must be destroyed to prevent—

(1) Its capture intact by the enemy.

(2) Its use by the enemy, if captured, against our own or allied troops.

b. The principles to be followed are:

(1) The destruction of matériel subject to capture or abandonment in the combat zone is undertaken only when in the judgement of the military commander concerned such action is necessary. *The destruction of matériel is a command decision to be implemented only on authority delegated by the division or higher commander.*

(2) Methods for the destruction of matériel subject to capture or abandonment in the combat zone must be adequate, uniform, and easily followed in the field.

(3) Destruction must be as complete as available time, equipment, and personnel will permit. If thorough destruction of all parts cannot be completed, the most important features of the matériel should be destroyed, and parts essential to the operation or use of the matériel which cannot be easily duplicated should be ruined or destroyed. The same essential parts must be destroyed on all like units to prevent the enemy from constructing one complete unit from several damaged ones by cannibalization.

c. Crews will be trained in the prescribed methods of de-

struction, but training will not involve the actual destruction of matériel.

d. Certain methods require special tools and equipment, such as TNT and incendiary grenades, which normally may not be items of issue. The issue of such special tools and matériel, the vehicles for which issued, and the conditions under which destruction will be effected are command decisions in each case, according to the tactical situation.

■ 31. ARMORED CARS.—*a.* To destroy vehicle see paragraph 15 of the appendix.

b. Whenever time and materials are available, combine the vehicle destruction outlined in paragraph 15 of the appendix with the armament and equipment destruction outlined in paragraph 16 of the appendix. If possible, detach and evacuate all machine guns mounted in the vehicle prior to destroying it. For additional methods, see FM 25-10.

■ 32. WEAPONS.—*a.* 37-mm gun.—To destroy 37-mm gun, see paragraph 16 of the appendix. For additional methods, see FM 23-81.

b. Small arms.—For details of destroying carbines and light machine guns, see FM 23-7 and FM 23-50, respectively.

■ 33. RADIO EQUIPMENT.—Secret and confidential equipment, codes, ciphers, cipher devices, and all instruction books will be destroyed beyond recognition when subject to capture or abandonment in the combat area. For details of methods to be employed for destroying various types of communication material, see FM 24-5. Radio sets may be destroyed by smashing with an ax or other heavy instrument. Dispose of broken equipment by burning or burying.

APPENDIX

	Paragraph
To mount.....	1
To close hatches.....	2
To open hatches.....	3
To dismount.....	4
To fight on foot.....	5
Inspection and maintenance before operation.....	6
Inspection during operation.....	7
Inspection at halt.....	8
Inspection after operation.....	9
To prepare to fire.....	10
Duties in firing.....	11
To suspend fire.....	12
To cease firing.....	13
To secure equipment.....	14
To destroy vehicle.....	15
To destroy weapons.....	16

■ 1. To Mount.—The crew, being at dismounted posts, mounts as follows:

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Commands MOUNT			
Executes about face.	Executes about face.	Executes about face.	Executes about face.
Mounts via mine rack on right side of car.	Mounts via right front of vehicle and takes mounted post on left side in bow of the car. (Does not pull or lean on muzzle of 37-mm gun.)	Mounts via left front of vehicle and takes mounted post on left side in bow of the car. (Does not pull or lean on muzzle of 37-mm gun.)	Mounts via mine rack on left side of car, and checks carrying position of guns so that hatch top covers may be closed.
Closes top cover of radio operator's hatch. Takes mounted post on right side of turret.			Closes top cover of driver's hatch and takes mounted post on left side of turret.
			Turns OFF-ON switch of radio receiver to ON. Turns OFF-ON switch of transmitter to ON. (Allows 30 seconds for receiver tubes to warm. Switches to assigned channel.)

Connects break-away plug. Connects break-away plug. break-away
Adjusts throat micro- Adjusts throat micro- Adjusts throat micro-
phone. phone. phone.

Turns radio interphone
switch to interphone,
depresses switch on
microphone cord,
and orders: **CHECK**
INTERPHONE.

Depresses switch on
microphone cord and
reports "Rad ready."

Depresses switch on
microphone cord and
reports "Driver
ready."

Depresses switch on
microphone cord and
reports "Gunner
ready."

Receives reports.
Reports "Car com-
mander ready."

■ 2. To CLOSE HATCHES.—The crew, being mounted, proceeds as follows:

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
---------------	----------------	--------	--------

Commands C L O S E
HATCHES.

Releases latch of driver's hatch front cover.

Releases latch of and closes his hatch front cover.

■ 3. To OPEN HATCHES.—The crew, being mounted, proceeds as follows:

C o m m a n d s O P E N
HATCHES.

Grasps hatch front cover handle and opens hatch.	Grasps hatch front cover handle and opens hatch.
--	--

■ 4. To Dismount.—The crew, being mounted, dismounts as follows:

Commands PREPARE

TO DISMOUNT.

Disconnects break-away plug.	Disconnects break-away plug.	Disconnects break-away plug.
Removes throat microphone.	Removes throat microphone.	Removes throat microphone.

Secures individual weapon.	Secures individual weapon.	Secures individual weapon.
----------------------------	----------------------------	----------------------------

Commands DISMOUNT.

Dismounts via mine rack on right side of car and takes his dismounted post three paces in front of the right front wheel, facing to the front.	Dismounts via right front of vehicle and takes his dismounted post on left of car commander at close interval (4 inches).	Dismounts via left front of vehicle and takes his dismounted post on left of radio operator at close interval (4 inches).	Dismounts via mine rack on left side of car and takes his dismounted post on left of driver at close interval (4 inches).
--	---	---	---

■ 5. To FIGHT ON FOOT.—The crew, being mounted, proceeds as follows:

GUNNER

DRIVER

RADIO OPERATOR

CAR COMMANDER

Commands FIGHT ON FOOT.

Hands two offensive grenades and one smoke grenade to radio operator.

Receives grenades from car commander.

Hands two offensive grenades and one smoke grenade to gunner. Secures individual weapon, ammunition, and dismounts.

Arms himself with two offensive grenades and two smoke grenades.

Receives grenades from car commander.

Hands four fragmenta-
tion grenades to
driver.

Dismounts coaxial ma-
chine gun and passes
it, together with one
box of caliber .30
machine-gun ammu-
nition, to radio op-
erator.

Receives grenades from
car commander.

Secures individual
weapon, ammuni-
tion, dismounts, re-
moves tripod for
LMG from fender
box.

Receives coaxial ma-
chine gun and box of
caliber .30 machine-
gun ammunition
from car com-
mander.

Secures individual
weapon, ammuni-
tion, and dismounts.

Receives box of caliber
.30 machine-gun am-
munition from gun-
ner.

Hands box of caliber
.30 machine - gun
ammunition to
driver.

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Receives tripod from driver, moves off; mounts tripod, mans gun as No. 1.	Follows car commander and takes position as No. 2.	Hands tripod for LMG to car commander.	Secures individual weapon, ammunition, and dismounts.
		Follows car commander and radio operator and takes position No. 3.	
			Follows car commander, radio operator and driver, and affords protection for LMG.

■ 6. INSPECTION AND MAINTENANCE BEFORE OPERATION.—The inspection and maintenance operation is divided into three phases to facilitate instruction. At the completion of this inspection, the car should be ready for operation. During training each phase should be ended by the car commander calling for a report. The crew, being formed dismounted, proceeds as follows:

Phase A

Commands INSPECT EQUIPMENT.		
Executes about face.	Executes about face.	Executes about face.

Mounts turret via right mine rack.	Checks radio antenna for breaks.	Looks at ground under car for oil and fuel leaks.	Mounts turret via left mine rack.
Removes turret opening canvas cover.	Checks radio antenna to determine that—	Checks lubricant in final drive, transfer case, and transmission. (This check should be made at least once per week.)	Assists car commander in removal of turret opening canvas cover.
Dismounts.	Mast sections are tight and taped.	Opens engine compartment. Checks engine oil, water level, generator belts, distributor wiring, air tube connections	Removes breech cover of turret guns.
Spreads turret opening canvas cover on ground at right of car.	Leads at transmitter, receiver, and mast base are tight.	from carburetors to air cleaners, and makes visual inspection of engine compartment.	Folds breech cover and places it on ground to right of turret opening canvas cover.
	Mast base is tight and not cracked.		
	Insulators passing through the armor plate are not broken or displaced.		
Removes canvas muzzle cover for 37-mm gun and coaxial machine gun.	Mounts.		Assists car commander in removal of canvas muzzle cover for 37-mm gun and coaxial machine gun.
Folds canvas muzzle cover and places it on ground to right of folded breech cover.	Checks radio set mountings, snaps, snubbers, and similar items.		

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Removes tool roll from right front fender box, opens roll, lays tools on turret opening cover and checks them.	Checks to see that microphones, keys, and headsets are in good condition and in their proper place.	Checks and cleans battery. (This should be done at least once per week. For continuous operation in hot weather, check twice per week.)	Enters turret and checks both guns to see that they are unloaded; leaves breechblock on 37-mm gun open.
Checks general condition of bogie, springs, shock absorbers, tie rod, drag link, wheels, and tires.	Replaces all defective headsets and microphones from spares. Turns in defective equipment for repair and replacement.	Closes engine compartment. Mounts.	Releases gun elevating lock. Checks gun elevating mechanism by fully depressing gun. Leaves gun elevated.
Assembles rammer staff and sponge.		Checks instrument panel to see that clutch pedal and transmission transfer case shift levers operate freely and over their full range.	Traverses turret 360°, centers gun, and depresses it for swabbing.
Swabs bore of 37-mm gun.			Checks hand and foot firing mechanisms for both guns.
Checks for presence and condition of fire extinguishers.			

Walks around vehicle checking for presence and condition of tow cable, pioneer tools, machine-gun tripod, tarpaulin, and lights.

Checks foot brake for 1/4-inch free travel.
Checks lights and siren (if permitted) with car commander.

Checks headspace and half loads machine gun if so directed.

Adjusts sights on 37-mm gun.

Inspects chamber and bore of both guns for dirt, obstructions, and lubrication.

Phase B

Signals driver to start engine.
Assists gunner to check oil in recoil mechanism.
Checks to see that spare antenna sections are in their proper place in the roll, and are stowed so that they will not be damaged or in the way of personnel.

Checks oil in recoil cylinder with aid of car commander.

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Stows tool roll.			
Stows or replaces canvas muzzle cover.	Checks to see that ground leads are connected at both ends.	Checks instruments and functioning of throttle, clutch, and steering levers.	Replaces breech covers if so directed. Closes breech lock.
Stows turret opening canvas cover.	Checks to see that tubes are firmly seated in sockets.		Checks and cleans periscope, periscope sight, spares, and checks knob setting on spare sights.
Replaces or stows breech cover for turret guns.	Checks for burned-out fuzes and is sure that adequate supply of spare fuzes of proper rating is on hand.		Checks pioneer compass against known direction.
Checks with driver on battery voltage.			Checks ammunition supply for quantity, type, stowage, and condition.

Phase C

Takes mounted post.	Takes mounted post.	Takes mounted post.
Connects break-away plug.	Connects break-away plug.	Connects break-away plug.

Adjusts throat micro- Adjusts throat micro- Adjusts throat micro-
phone. phone. phone.

With control box on
RAD, if tactical
situation permits,
checks transmission
and reception with
other cars.

C h e c k s interphone
system and calls for
report from crew
members.

Adjusts volume. Adjusts volume.

Reports "Rad ready."

Reports "Driver
ready."

Reports "Gunner
ready."

Reports "Car com-
mander ready."

■ 7. INSPECTION DURING OPERATION.—During operation inspection is continuous. Duties are:

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Remains constantly alert to detect unusual noises and conditions.	Remains constantly alert to detect unusual noises and conditions.	Checks instruments continually.	Checks to assure that 37-mm gun is securely locked in place.
Checks to assure that coaxial machine gun is securely locked in place.		Listens for unusual noises. Detects abnormal functioning of engine.	Checks to assure that stowage is securely fastened in place.
		Checks steering mechanism to detect faults.	
Checks reading of hull compass against known direction.		Checks, by application of brakes and opening of throttle, any missing cylinders. (This is done just before operation is completed.)	Checks condition of antenna mast and mast base on left.
Occasionally checks operation of interphones.			
Checks operation of radio if tactical situation permits.			
Listens on radio except when interphone is being used.			

Maintains constant check on stowage of equipment.
Checks condition of antenna mast and mast base on right.

■ 8. INSPECTION AT HALT.—At a short halt the vehicle is inspected as follows:

Commands MAKE HALT INSPECTION.

Disconnects break-away plug and removes throat microphone.	Disconnects break-away plug and removes throat microphone.	Disconnects break-way plug and removes throat microphone.	Remains in turret. Acts as air and ground observer.
Dismounts.	Drains oil that may have leaked onto hull floor, after correcting the cause of leakage.	Dismounts.	Tends radio.
Examines wheels, tires, steering, linkage, front axle, and bogie for adjustment and for worn, loose, broken, or missing parts.	Dismounts.	Checks oil level.	
	Inspects lights if traveling at night with lights.	Checks fuel level.	
		Checks water level.	Checks sight adjustment.

GUNNER

DRIVER

RADIO OPERATOR

CAR COMMANDER

Inspects hull and fittings for worn, missing, or loose parts.

Cleans all vision devices. Cleans trash from and inspects suspension system.

Acts as sentry during sight adjustment.

■ 9. INSPECTION AFTER OPERATION.—After operation, when vehicle has been moved into bivouac or motor pool, a complete inspection is made of all equipment; fuel oil and ammunition are replenished. The crew proceeds as follows:

Phase A

Commands INSPECT EQUIPMENT.

Disconnects break-away plug.

Disconnects break-away plug.

Disconnects break-away plug.

Disconnects break-away plug.

Removes throat microphone.

Removes throat microphone.

Removes throat microphone.

Removes throat microphone.

Dismounts.

Dismounts.

Dismounts.

Turns OFF-OFF switch

of radio receiver to OFF.

Removes turret canvas opening cover from fender box.	Assists driver.	Checks engine operation, all instruments, ignition, and siren.	Turns OFF-ON switch of radio transmitter to OFF.
Spreads turret canvas opening cover on ground at right of car.			
Takes breech cover and canvas muzzle cover from gunner, folds and places them on ground at right of turret opening cover.			Passes breech cover and canvas muzzle cover to car commander.
Checks tools and places them on turret opening cover.			Checks 37-mm gun and coaxial machine gun to see that they are unloaded.
Checks lights.	Mounts.	Checks lights with car commander.	Cleans and lubricates machine gun to extent permitted by tactical situation.

Phase B

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Assembles cleaning staff.	Moves car as required for inspection of suspension system. Stops engine.	Inspects wheels, tires, steering linkage, front axle, and bogie for adjustment and for worn, loose, broken, or missing parts.	Checks periscope head and spares for damage and cleanliness. Cleans periscope head.
			Removes loose rounds and empty cases from car.
		Checks lubricant in final drive.	Checks ammunition and notes expenditure of ammunition for report to car commander.
	Checks spare parts for radio(s).		Checks spare parts for guns.
Swabs bore of 37-mm gun.			Cleans and lubricates breech mechanism of 37-mm gun.
Reassembles cleaning staff.			Assists car commander in checking recoil oil.
Checks recoil oil.			

Phase C

Inspects hull and fittings for worn, missing, or loose parts. Inspects all control linkage to locate loose or broken parts. Checks, cleans, and refills air cleaner with clean oil during extremely dusty operations. Cleans all vision devices.

Inspects electrical wiring for loose connections.

Cleans crankcase breather and replenishes oil. Replenishes engine oil.

Replenishes water. Checks condition of battery. Replenishes battery water.

Removes and checks fire extinguisher. Checks servicing of weapons.

Phase D

Directs replenishing of fuel.

Stows tools.

Stands ready with fire extinguisher to put out fire while driver fills vehicle tank. Replenishes fuel. Replaces breech cover.

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Passes ammunition to gunner. Places turret opening cover to gunner and assists gunner in placing it over turret opening.	Replaces fire extinguisher.		Receives and stows ammunition. Places turret opening cover over turret, assisted by car commander.
	Cleans driver compartment.	Assists radio operator in cleaning driver compartment.	
Replaces canvas muzzle cover.			Assists car commander in replacing canvas muzzle cover. Reports condition and amount of ammunition, supplies, and equipment, and any other pertinent information to car commander.
Completes trip ticket, reports all accidents, malfunctions, and requirements for maintenance, supplies, and ammunition to platoon leader.			

NOTE.—Members of crew perform such necessary maintenance as possible during inspection.

■ 10. TO PREPARE TO FIRE.—Before engaging in range firing or when action is imminent, the car is prepared for firing as follows:

Commands PREPARE

TO FIRE.

Assists gunner in removal of breech cover.

Inspects ammunition for proper amount, types, loading, and cleanliness. Removes gun cover of 37-mm gun and coaxial machine gun.

Checks to see that no empty cases are on floor. Closes hatch front cover.

Closes hatch cover. front Removes breech cover of guns.

Installs and checks sight on 37-mm gun. Checks sight for cleanliness.

Checks guns for cleanliness and lubrication.

Reports "Rad ready."

Reports "Driver ready."

Disconnects gun mount traveling lock.

Checks traversing and elevating mechanisms.

CAR COMMANDER RADIO OPERATOR DRIVER GUNNER

Checks trigger actuator mechanisms.

Opens 37-mm breech lock and inspects bore for obstructions; closes breech lock.

Places box of caliber .30 ammunition in machine-gun rack.

Checks radio to make sure it is operating properly.

Reports "Gunner ready."

Checks operation of breech lock.

Receives report from crew members.

Reports "Car commander ready."

■ 11. DUTIES IN FIRING.—The car being prepared for action, the crew executes the following:

Loads 37-mm gun. Operates radio.

Gives fire order.

Controls and adjusts fire by sensing strike or trace and announces appropriate changes of range and deflection to gunner.

Controls driver so that car operates tactically with rest of platoon.

Signals "Ready" each time 37-mm has been reloaded. (Touches leg of gunner with his foot to indicate gun is loaded.)

Fires on targets designated by car commander. Continues fire until target is destroyed, new target is designated, or CEASE (SUSPEND) FIRING is given.

Drives in direction indicated by car commander. Operates car at a constant speed. Does not deviate from designated course except to avoid large obstacles. Announces "Changing course" or "rough" when necessary.

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Inspects each round of 37-mm ammunition before loading. Watches recoil and counter-recoil of gun and indicates any necessary adjustments to gunner. Reduces malfunctions in coaxial machine gun. Fires antiaircraft gun, if vehicle is so equipped, during air attack.			Informs car commander if caliber .30 machine gun fails to fire by calling "Jam." Traverses turret, as ordered by car commander, when anti-aircraft machine gun is being fired.

■ 12. To SUSPEND FIRE.—The crew proceeds as follows:

Commands SUSPEND
FIRE.

Operates car as or-
dered. Ceases firing.

Reloads 37-mm gun, if Operates radio.
unloaded.

Puts safety on SAFE.

Unloads or orders fire
re s u m e d before
round heats.

Observes and lays on
target or lays on new
target if directed.

■ 13. To CEASE FIRING.—The crew proceeds as follows:

Unloads 37-mm gun if Operates radio.
loaded.

Operates car as or-
dered. Ceases firing.

Observes for new tar-
gets.

Assists in replenishing
the ready racks.
Observes for new tar-
gets.

Orders and assists in
the shifting of am-
munition as required.

Traverses turret as di-
rected by car com-
mander.

■ 14. To SECURE EQUIPMENT.—After firing, when car is to be moved, the crew proceeds as follows:

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Commands SECURE EQUIPMENT.			
When gun is traversed to straight ahead position, assists gunner in setting gun mount traveling lock.			Traverses turret to straight ahead position.
Assists gunner in replacing breech cover for turret guns.	Opens hatch front cover.	Opens hatch front cover.	Replaces breech cover of turret guns.
Checks ammunition and replenishes if necessary.			Replenishes caliber .30 machine - gun ammunition, if necessary.
	Reports "Rad ready."	Reports "Driver ready."	Reports "Gunner ready."
Receives reports from crew members.			
Reports "Car commander ready."			

■ 15. To DESTROY VEHICLE.—It may be necessary to abandon and destroy the vehicle and equipment to prevent its capture by the enemy. (See par. 31.) When the command **ABANDON AND DESTROY VEHICLE** is given, the crew proceeds as follows:

Time required: 1 to 2 minutes

Punctures gas tank. Removes and empties Places 2-pound TNT
Pours gasoline over portable fire extin- charge against clutch
each tire. (When guishers. housing, side of cyl-
combined with de- in der block, the
struction of vehicle transmission hous-
by TNT, fires should ing, or transfer case.
be well started before
detonating TNT.)

Reports "Rad ready."

Reports "Driver ready."

Inserts tetryl nonelec-
tric caps with at least
5 feet of safety fuze
in each charge.
Reports "Gunner
ready."

Receives reports.
Commands **IGNITE**.
Takes cover.

Takes cover.

Takes cover.

Ignites fuzes and takes
cover.

- 16. TO DESTROY WEAPONS.—The destruction of the 37-mm gun is accomplished by one or a combination of the following methods (see par 32):

Method No. 1

Time required: 2 to 3 minutes, if ramrod is used to plug bore and cut-down TNT is carried with car

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Opens drain plug on recoil mechanism, allowing recoil fluid to drain.	Assists car commander and driver.		Detaches all optical sights. (If evacuation is possible, carries sights; if evacuation is not possible, thoroughly smashes sights.)
Removes HE shell from a complete round and seats shell in chamber.			

Cuts down a ½-pound TNT block to fit snugly in chamber behind the HE shell.

Plugs bore for approximately two-thirds of its length, using a ramrod wrapped with cloth or waste to make it fit tightly in the bore. (Mud, stones, or clay may be used in lieu of the ramrod.)

Inserts a tetryl non-electric cap, with approximately 3 or 4 feet of safety fuze into TNT block. Closes breech as far as possible.

Ignites safety fuze and takes cover 100 yards from gun.

Takes cover 100 yards from gun. Takes cover 100 yards from gun. Takes cover 100 yards from gun.

Method No. 2

Time required: 1 to 2 minutes using ramrod to plug the bore; longer if the bore is plugged with mud or other material.

CAR COMMANDER	RADIO OPERATOR	DRIVER	GUNNER
Opens drain plug on recoil mechanism, allowing recoil fluid to drain.	Duties are same as prescribed in Method No. 1.	Plugs bore for approximately two-thirds of its length, using a ramrod wrapped with cloth or waste to make it fit tightly in the bore. (Mud, stones, or lay may be used in lieu of the ramrod.)	Duties are same as prescribed in Method No. 1.
Inserts one complete HE round into gun and closes breech.			
Takes cover and fires gun, using a lanyard 100 feet long.	Takes cover 100 yards from gun.	Takes cover 100 yards from gun.	Takes cover 100 yards from gun.

Method No. 3

Time required: 2 to 3 minutes

Opens drain plug on re- Takes cover.

coil mechanism, al-
lowing recoil fluid to
drain.

Inserts HE shell in
chamber and closes
breech.

Takes cover and fires
gun using a lanyard
100 feet long.

Duties are same as pre-
scribed in Method
No. 1.

Jams HE shell in
muzzle.

Takes cover.

Takes cover.